

Model
600 Endeavour



New!

Indicative rendering

600 Endeavour

LENGTH (LMAX) CM	MAX. BEAM CM	DRY WEIGHT KG	PEOPLE CARRYING CAPACITY
599	263	480	14

TECHNICAL CHARACTERISTICS AND FEATURES

MODEL	600 ENDEAVOUR
Length (Lmax) cm	599
Int. length cm	550
Max. beam cm	263
Int. width cm	143
Construction height cm	92
Tubular diameter cm	50÷60
Motor shaft version	1 L
Number of compartments	5
Number of lockers	6
"Dry weight (excluding motor, fittings and liquids) Kg"	480
People carrying capacity	14
"Max. carrying load Kg (Number of people + standard equipment + engine)"	1500
Inflation pressure atm	0,2
Max. applicable power Kw (HP)	126 (171)
Recommended power HP (Min/Max)	80 / 115
Hull type	Deep-V with rest skids
Hull material	VTR = double shell
Hull internal colour	Grey
Hull external colour	Grey
Fabric	Neoprene - Hypalon, 1300 g/mq
EC standard design category	C

For information on engines in packages with Endeavour Line boats, see outboard engine catalogue.

The data contained in these tables are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

The specifications given in this table are determined in accordance with the regulations in force at the time of writing the catalogue and may have to be changed in case of variation of the technical rules of reference. We invite you to request the confirmation of the data in force at the time of product purchase.

MODEL	600 ENDEAVOUR
Tubular double colour grey / black carbon impression	S
Handrail in fabric on tubular	S
Pair of oars	S
Inflating pump	S
Motor installation	S
Complete electrical system	S
Starter battery with box and cut-off switch	S
Complete console (1)	S
Steering wheel "Special"	S
Pair of twin jockey seats	S
Engine instrumentation	S
Foldable stern couch	S
Bow locker cushions	S
Bow sundeck extension	O
Cushion for bow sundeck extension	O
Cushions "Endeavour" bi-colours	S
FRP stern dashboard with stainless steel ladder	S
Auxiliary motor support	O
Sun awning	O
Foldable "Twin-tube" stainless steel, telescopic, tip-up rollbar with start lights and horn	O
Mooring cover	O
"Built-in fuel tank installed in compliance with CE regulations with blower, delivery pipe with water/fuel separating filters and solenoid valves, filling pipe, breather pipe and fuel level gauge."	S - 150 lt.
Immersion bilge pump	S
hydraulic steering system	O

S= Standard O= Optional

(1) Console complete with: stainless steel lifeline, single-lever remote-control box, anatomic steering wheel, singlecable steering gear, anti-reflection windscreen, door with lock, front seat with cushion and access to locker underneath plus back-rest cushion.

On the Selva Marine engines 5 years limited warranty under certain conditions and exclusions. It is not applicable for professional use.